

# Exit LED

Indoor LED exit sign



## Optics

- Power consumption:
  - 3W maintained
  - 1.5W non maintained
- 16 x low energy LEDs
- 36m viewing distance
- Product is supplied as a complete unit with opal polycarbonate legend panel already fitted
- Up, down, left and right legend panels are available
- Legends supplied in accordance with BS 5266-1 2011 (ISO7010)

## Body

- Wall mounted via key hole slot fixings
- Steel body finished white
- Two part body for ease of installation, cover hooks over the back plate and is simply retained below
- High temperature Ni-Cd battery with constant current charger and LED charge indicator
- 3 hour maintained (may be wired as non-maintained)
- BESA cable entry

# Order codes

3W, with UP legend supplied	EXM7010U
3W, with LEFT legend supplied	EXM7010L
3W, with RIGHT legend supplied	EXM7010R
3W, with DOWN legend supplied	EXM7010D

## Options

COMEPS                                      Add suffix /EP                                      i.e EXM7010U/EP

## Dimensions

L	W	H	KG
385	71	185	2.4

## To Specify

3W LED IP20, 3 hour self-contained maintained emergency exit sign with rigid white powder coated steel body and opal polycarbonate legend. High temperature Ni-Cd battery with constant current charger and LED charge indicator - as Whitecroft Lighting EXIT LED